


CLIPPER[®]



8+
BENEFITS



CLIPPER GLITTER

Admixture For Sparkling Joints

TILE & STONE SOLUTIONS

Areas of Application

Clipper Glitter is a special admixture to be mixed with Clipper Clippoxy for sparkling & shining tile & stone joints. This glitter effect enhances the beauty of the tiling. It is ideal to use for domestic as well as commercial applications.

- Add with Clipper Clippoxy For Sparkling Joints
- In Internal & External Areas • Wet & Dry Conditions on Floor & Wall

Benefits

- Excellent Glitter Effect
- Multiple Attractive Colours
- Stain-Free
- Easy to Use
- Easy to Dissolve
- Chemical Resistant
- Water Resistant
- Eco-Friendly

Colour

Available in Silver, Gold, Copper & Rainbow colour.

Additional Info

Get over 100 different sparkle effects by using the colours in varying combinations.

Technical Specifications

| | |
|-------------------------|------------------------|
| Density | 1.5 g/cc |
| Mixed Density | 1.75 +/- 0.05 kg/litre |
| Pot Life | upto 1 hour |
| Water Solubility | Insoluble |
| Light Foot Traffic | 24 hours |
| Regular Traffic | 72 hours |
| Recommended Joint Width | 2 mm - 15 mm |

Pack Size

30 g & 150 g

Shelf Life

1 year from the date of manufacturing.

Clipper Construction Chemicals Pvt. Ltd. (An ISO 9001:2015 Certified Company)

200/2, Bhawrasla, Sanwer Road, Indore,
Madhya Pradesh - 453555 INDIA

 **62 62 055 055**

Email: info@clipperchemicals.com

Website: www.clipperchemicals.com

 /ClipperChemicals

 /ClipperChemicals

 /ClipperChemical

 /company/Clipper-Chemicals

 /ClipperChemicals



TILE & STONE FIXING



WATERPROOFING



CLIPPER CARE RANGE



PLUMBING SOLUTIONS

Health and Safety - We strongly recommend to follow all safety guidelines applicable under all construction settings. We suggest the usage of gloves and goggles. Any splashes to skin or eyes should be washed off immediately with clean water. If irritation persists, take advice from a qualified healthcare professional immediately.

Disclaimer - All the information mentioned on this product information sheet is to be considered as a general guideline. The actual usage and results may vary from condition to condition. We advise undertaking a trial in user-specific conditions before full-scale usage. We do not commit any express or implied guarantee/warranty for the results. The company is not liable for any consequential loss or damage.