













Tint to Desired

Shades



Impermeability

CO2



Microbial Resistance

~`' <u>Y</u> Y

Crack Bridging



DAMP-PROOF HATTRICK

3 in 1 Solution - Waterproofing, Coating, Priming

DAMP-PROOF HATTRICK

Areas of Application

Clipper Damp-Proof is a fibre reinforced elastomeric, super flexible acrylic waterproofing coating for terrace and external walls. Its thick membrane provides crack bridging ability and ultimate waterproofing to the cementitious substrates.

- Waterproofing Coating For Terrace & Wall
 Flat & Slope Roof
- Over Cementitious Substrates

Benefits

- 10 Years Performance Warranty
- Impermeability
- Crack Bridging
- Reduces Surface Temperature
- Anti-Carbonation
- Microbial Resistance
- Tint to Desired Shades
- Economical

Form

Ready to use single component viscous liquid.

Colour

White

Coverage

It covers an area of approx ~20-25 sq.ft per litre.

Technical Specifications

Elongation at Break	> 150%
Mix Density	1.3
Adhesion Strength	>1N/mm²
Water Absorption	> 20%
Hydrostatic Pressure	7 bar passes
Tensile Strength	1.5 MPa
Crack Bridging	No Cracks upto 1 mm
Drying Time to Touch	4-6 hours

Pack Size

1 litre, 4 litre & 20 litre

Shelf Life

2 years from the date of manufacturing.

Clipper Construction Chemicals Pvt. Ltd.

(An ISO 9001:2015 Certified Company)

200/2, Bhawrasla, Sanwer Road, Indore, Madhya Pradesh - 453555 INDIA



Email: info@clipperchemicals.com Website: www.clipperchemicals.com







WATERPROOFING





Health and Safety - We strongly recommend to follow all safety guidelines applicable under all construction settings. We suggest the usage of gloves and goggles. Any splashes to skin or eyes should be washed off immediately with clean water. If irritation persists, take advise from a qualified healthcare professional immediately.

Disclaimer - All the information mentioned on this product information sheet is to be considered as a general guideline. The actual usage and results may vary from condition to condition. We advise undertaking a trial in user-specific conditions before full-scale usage. We do not commit any express or implied guarantee/warranty for the results. The company is not liable for any consequential loss or damage.