



















High Pressure







# **PVC SOLVENT**





## Areas of Application

**Clipper PVC Solvent** is regular bodied, high pressure and high strength solvent cement used for all classes and schedules with interference fit through 12" diameter. For use with rigid / SWR / PVC pipes and fittings.

- Potable Water, Non-pressure Pipe, SWR/Rigid Pipes and DWV
- Filling Gaps in Large Diameter Pipe and Loose Fitting Joints
- Through 12" diameter

#### Benefits

- Regular Bodied
- Slow Setting
- · High Strength
- High Pressure
- Good Gap Filling
- Long Working Time

#### Colour

Clear

#### Caution

Store product below 44°C (111°F)

## Technical Specifications

Brookfield Viscosity	Min. 90 cP
----------------------	------------

#### Pack Size

25 ml, 50 ml, 100 ml, 250 ml, 500 ml, 1 litre & 5 litre

## Shelf Life

2 years from the date of manufacturing.



## Clipper Construction Chemicals Pvt. Ltd. (An ISO 9001:2015 Certified Company)

200/2, Bhawrasla, Sanwer Road, Indore, Madhya Pradesh - 453555 INDIA



**Email:** info@clipperchemicals.com **Website:** www.clipperchemicals.com



O /ClipperChemicals

X /ClipperChemical

in /company/Clipper-Chemicals

/ClipperChemicals









Health and Safety - We strongly recommend to follow all safety guidelines applicable under all construction settings. We suggest the usage of gloves and goggles. Any splashes to skin or eyes should be washed off immediately with clean water. If irritation persists, take advise from a qualified healthcare professional immediately.